

KV-S7097 KV-S7077

Improve Your Work Efficiency with Dual Scanning





High-Speed Scanning

A4, Landscape, 300 dpi, Binary/Colour

100 ppm / 200 ipm (KV-S7097) 75 ppm / 150 ipm (KV-S7077)



- ✓ ADF / Flatbed Scanning
- √ Single Touch Scanning
- ✓ Multi-Crop
- ✓ Double-Feed Skip









Hardware Image Processing (ADF Only)

Drops in the scanning speed can be minimised by using hardware for frequently used image processing.

Specifications

Scanning Face	Duplex & Flatbed
Scanning Method	ADF: 3-line colour hybrid CIS (Front and back sides),
ocaniming incentor	Flatbed: 3-line colour hybrid CIS
Scanning Resolution*1	100 dpi - 600 dpi (1 dpi step) and
occining resocution	1,200 dpi (software) (Optical 600 dpi)
Scanning Speed*2	KV-S7097
	ADF: Landscape / A4, Simplex: 100 ppm, Duplex: 200 ipm
	Flathed: 0.8 sec. [A4 / Portrait]
	KV-S7077
	ADF: Landscape / A4, Simplex: 75 ppm, Duplex: 150 ipm
	Flatbed: 0.8 sec. (A4 / Portrait)
Double-Feed Detection	Ultrasonic (The length of documents that can be detected is
Bodble Feed Bettettion	70 mm or more.)
Image Compression	MH. MMR (Software ICP), JPEG
Binary Mode Halftone	Dither, Error Diffusion
Document Size ADF	Manual feeding: 48 × 70 mm (1.9 × 2.75 in.) to
	302 mm × No Limited (11.9 in. × No Limited)
	Automatic feeding: 48 × 70 mm (1.9 × 2.75 in.) to
	302 × 432 mm (11.9 × 17 in.)
Flatb	med Maximum size: 297 × 432 mm (11.7 × 17 in.)
Document Weight	31 - 127 g/m² (8.3 - 34 lbs.)*3,
	Smaller than A7 size: 127 g/m² (34 lbs.) only
Feed Tray Capacity	200 sheets: 80 g/m² (21lbs.)
Supported Operating System	Windows Vista® SP2 (32 bit/64 bit),
	Windows® 7 (32 bit/64 bit), Windows 8 (32 bit/64 bit),
	Windows 8.1 (32 bit/64 bit), Windows 10 (32 bit/64 bit),
	Windows Server® 2003 SP2 (32 bit/64 bit), Windows Server®
	2003 R2 SP2 (32 bit/64 bit), Windows Server® 2008 SP2
	(32 bit/64 bit), Windows Server® 2008 R2 SP1 (64 bit), Windows
	Server® 2012 (64 bit) ,Windows Server® 2016 (64 bit), Red Hat®

*1 When scanning a document larger than A5 size at high resolutions over 600 dpi, the scanning may fail due to insufficient memory. *2 The scanning speed differs depending on the host computer, the operating system, the application, the measuring method, the quantity of data in the image, and the paper type. The scanning speed depends on a measuring method of Panasonic. *3 Use "Thin Paper Feeding Mode" when scanning the document less than 40 g/m" 10.6 lb.]. For details about "Thin Paper Feeding Mode", refer to the Image Capture Plus, TWAIN, or ISIS help. *4 About the environmental conditions of Imprinter Unit (IWC-SS014), refer to the Tinformation" leaflet of the optional imprinter unit. When printing in conditions outside of the imprinter unit's operating environment, the printing result may be faded or printing may not occur.

Digital Imprinter

The "Digital imprinter" enables additional printing to the scanned image data.

Interface		USB 3.1 Gen1 (backward compatible)
External Dimensions (W X D X H)		755 x 508 x 289 mm (29.7 x 20.0 x 11.4 in.)
Weight		29.0 kg (64 lbs.), 30.0 kg (66 lbs.) include accessories
Power Requirement		AC 100-127 V, 50/60 Hz, 1.5 A
		AC 100-240 V, 50/60 Hz, 1.5-0.8 A
		AC 220-240 V, 50/60 Hz, 0.8 A
Power	Maximum	00 W 4 F 4 (400 40F) (1 00 W 0 0 4 (000 0 (0))
Consumption	(Scanning)	90 W: 1.5 A (100-127 V), 90 W: 0.8 A (220-240 V)
·	Minimum	00 W (400 40F V / 000 0 /0 V)
	(Ready)	38 W (100-127 V / 220-240 V)
	Sleep	1.4 W or less (100-127 V / 220-240 V)
	Power Off	0.3 W or less (100-127 V / 220-240 V)
Operating Environment *4		Temperature: 5 °C to 35 °C (41 °F to 95 °F)
		Humidity: 20 % RH to 80 % RH (No dewdrop)
Storage Environment *4		Temperature: -10 °C to 50 °C (14 °F to 122 °F)
		Humidity: 8 % RH to 75 % RH (No dewdrop)
Accessories		CD-ROM: Device driver, ISIS driver software,
		TWAIN driver software, WIA driver software, User utility,
		Scan Button Setting Tool, Image Capture Plus with OCR Engine,
		Operating Manual, Control data sheet (PDF)
		Quick Installation Guide, Power Cord, USB Cable (USB 3.1),
		Shading paper, Hopper tray
Options		Roller exchange kit: KV-SS015, Roller cleaning paper: KV-SS03,
		Imprinter Unit (Pre): KV-SS014, Ink cartridge: KV-SS021

Trademarks and registered trademarks

- ENERGY STAR and the ENERGY STAR mark are registered U.S. marks.
 ISIS is a registered trademark or trademark of Open Text Corporation.
 Windows, Windows Vista and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

 Linux is a registered trademark or a trademark of Linux Torvalds in the United States and other countries.

 Linux is a registered trademark or a trademark of Linux Torvalds in the United States and other countries.

 Red Hat and Red Hat Enterprise Linux are registered trademarks or trademarks of Red Hat, Inc. in the United States and other countries.

 - Ubuntu is a registered trademark or a trademark of Canonical Ltd. in the United States and other countries.

- All other brand or product names are the property of their respective holders.
 This product is designed to reduce hazardous chemical substances in accordance with the RoHS directive.
- * The power requirement differs depending on the country/area. · All photographs in this brochure are simulated

As an ENERGY STAR® partner,

Panasonic has determined that this

product meets the ENERGY STAR , guidelines for energy efficiency.

- Weights and dimensions are approximate.
 Specifications are subject to change without notice.
 These products may be subject to export control regulations.











DISTRIBUTED BY:

